





AROMA

**Vetrine refrigerate statiche o ventilate per l'esposizione di vini spumanti, vini bianchi e vini rossi.**

- Colore standard: stile inox satinato
- Doppia illuminazione verticale a led
- Porta a basso emissivo, dotata di vetro panoramico per ampia visibilità
- Modelli con posizionamento bottiglie su tubi in acciaio (T) o su **ripiani inox forati (optional)**
- Solida maniglia in acciaio inox con serratura
- Controllo elettronico della temperatura posto nella parte superiore della vetrina.

**N.B.:** Per installazioni ad altitudini superiori a 900 m s.l.m., deve essere prevista e specificata al momento dell'ordine una valvola di compensazione per ogni vetrocamera.



Doppia illuminazione a LED  
Double LED lighting



Tubi di appoggio bottiglie cromati  
Chromed support for bottles

**Static or ventilated wine display for all kind of sparkling, white or red wines.**

- Standard color: Brushed s/s style
- Double vertical LED lighting
- Door with reduced thermal losses, with large panoramic glass for wide visibility
- Models with bottles' positioning on stainless steel tubes (T) or **perforated stainless steel shelves (optional)**
- Sturdy s/s handle with lock
- Electronic control panel positioned in the upper part of the showcase.

**N.B.:** For installations at altitudes above 900 m (above sea level), a compensating valve for each double-glazing unit must be provided and specified at the time of the order.



Ripiani inox forati (optional)  
S/s shelves (optional)



Elegante maniglia in acciaio inox con serratura  
Elegant design s/s handle with lock

	Modello Model	Codice Code	N° Bottiglie Nr Bottles ø77	Refrigerazione* Refrigeration*	Range Range (°C)	Gas Gas	Accessori** Accessories**	Dimensioni Dimensions (mm)	Assorbimento Absorbed power		Classe climatica Climate class	Alimentazione Power Supply (V/hz)	Dimensioni imballo Packing dimensions (mm)	Peso Netto/Lordo Net/Gross weight (kg)	
									Watt****	Ampere					
	<b>AROMA 610 S T</b>	6AROM610SA000	74 su tubi/on tubes  (102 su ripiani/on shelves)	S	0/+15°	R290 GWP 3 Kg 0,90	TUBI ACCIAIO S/S TUBES	610x515x1940	247	5.03	3 25°C - 60%	230/1/50	650x550xh2200	103/115	
	<b>AROMA 610 V T</b>	6AROM610VA000	74 su tubi/on tubes  (102 su ripiani/on shelves)	V	0/+15°		TUBI ACCIAIO S/S TUBES	610x515x1940	247	5.03	3 25°C - 60%	230/1/50	650x550xh2200	104/116	
	<b>AROMA 820 S T</b>	6AROM820SA000	113 su tubi/on tubes  (153 su ripiani/on shelves)	S	0/+15°	R290 GWP 3 Kg 0,100	TUBI ACCIAIO S/S TUBES	820x515x1940	247	5.03	3 25°C - 60%	230/1/50	880x550xh2200	120/135	
	<b>AROMA 820 V T</b>	6AROM820VA000	113 su tubi/on tubes  (153 su ripiani/on shelves)	V	0/+15°		TUBI ACCIAIO S/S TUBES	820x515x1940	247	5.03	3 25°C - 60%	230/1/50	880x550xh2200	121/136	
		72538296	Ripiano Inox forati (mod. AROMA 610)					Drilled s/s shelves (mod. AROMA 610)							
		72538294	Ripiano Inox forati (mod. AROMA 820)					Drilled s/s shelves (mod. AROMA 820)							
	<b>VERS220-1-60AROMA</b>		Sovraprezzo Versione 220V/1Ph/60Hz - GAS R404a (Disponibile non prima di 6 settimane)					Price increase for 220V/1Ph/60Hz Version - GAS R404a (Available not earlier than 6 weeks)							

\*S= STATICA / STATIC - V=VENTILATA / VENTILATED

\*\* T=TUBI ACCIAIO / S/S TUBES \*\*\*\* Watt TN (-10/+45°C)

I gas fluorati a effetto serra sono contenuti in apparecchiature ermeticamente sigillate.

Dati tecnici e caratteristiche soggetti a cambiamento senza preavviso.

Refrigerant gases are contained in hermetically sealed equipment

All specifications are subject to change without notice.