



TRK
602/3/4




Mesas refrigeradas ventiladas sobre patas, profundidad 700 mm en acero prelacado STEEL-PET, encimera de trabajo de acero inoxidable AISI 304, 2, 3 o 4 compartimientos 1 rejilla plastificada 400x600 sobre guías en C (mod.C) o 3 par guías acero inoxidable en L (mod.L) para puerta.

- Grupo incorporado
- Encimera recta, con alzada o sin encimera
- Controlador digital
- Descongelación y evaporación del agua de condensación automáticas.

S/s AISI 304 ventilated refrigerated counters on feet, 600 mm of depth; 2, 3 or 4 doors for 430x325 mm shelves, with 1 plastic coated shelf per door or 1/2 or 1/3 drawers.

- Built in unit
- Versions with straight worktop, worktop with splashback or without top
- Digital controller
- Automatic systems for defrosting and evaporation of the condensation water (only models with built-in unit)

OPTIONALS



74768132



SOVVCAS1/2



SOVCAS1/3



	Modelo <i>Model</i>	Código <i>Code</i>	Encimera <i>Worktop</i>	Rango <i>Range</i>	GAS <i>GAS</i>	Clase energética <i>Energy class</i>	Clase climática <i>Climate class</i>	Consumo eléctrico anual <i>Annual electricity consumption</i>	Volumen útil neto <i>Net storage volume L</i>	Dimensiones <i>Dimensions</i> mm	Absorción <i>Absorbed power</i>		Alimentación <i>Power supply</i> (Volt/Ph/Hz)	Dimensiones embalaje <i>Packing dimensions</i> mm	Peso Neto/Bruto <i>Net/Gross weight</i> Kg
											Watt****	A			
	TRK602 TN/A	9TRK62IPLA021	Encimera con alzada - <i>with work top with splashback</i>	0/+8° C	R290-GWP 3 Kg 0,085	B	5 40°C - 40%	712	136	1260x600x950	210	1,32	230/1/50	1320x750x1100	76/98
	TRK602 TN/S	9TRK62IPNA021	Sin encimera - <i>without work top</i>	0/+8° C		B	5 40°C - 40%	712	136	1260x600x810	210	1,32	230/1/50	1320x750x1100	76/98
	TRK602 TN	9TRK62IPVA021	Encimera recta - <i>straight work top</i>	0/+8° C		B	5 40°C - 40%	712	136	1260x600x850	210	1,32	230/1/50	1320x750x1100	76/98
	TRK603 TN/A	9TRK63IPLA021	Encimera con alzada - <i>with work top with splashback</i>	0/+8° C	R290-GWP 3 Kg 0,085	B	5 40°C - 40%	803	204	1720x600x950	210	1,32	230/1/50	1760x750x1100	106/133
	TRK603 TN/S	9TRK63IPNA021	Sin encimera - <i>without work top</i>	0/+8° C		B	5 40°C - 40%	803	204	1720x600x810	210	1,32	230/1/50	1760x750x1100	106/133
	TRK603 TN	9TRK63IPVA021	Encimera recta - <i>straight work top</i>	0/+8° C		C	5 40°C - 40%	859	204	1720x600x850	210	1,32	230/1/50	1760x750x1100	106/133
	TRK604 TN/A	9TRK64IPLA021	Encimera con alzada - <i>with work top with splashback</i>	0/+8° C	R290-GWP 3 Kg 0,100	C	5 40°C - 40%	1022	272	2180x600x950	260	1,8	230/1/50	2250x750x1100	121/153
	TRK604 TN/S	9TRK64IPNA021	Sin encimera - <i>without work top</i>	0/+8° C		C	5 40°C - 40%	1022	272	2180x600x810	260	1,8	230/1/50	2250x750x1100	121/153
	TRK604 TN	9TRK64IPVA021	Encimera recta - <i>straight work top</i>	0/+8° C		C	5 40°C - 40%	1094	272	2180x600x850	260	1,8	230/1/50	2250x750x1100	121/153
		74768132	Rejilla plastificada 430x325		Plastic coated 430x325 shelf										
		74701947 P600x2	Par guías acero inoxidable (450 mm)		S/s pairs of runners (450 mm)										
	VERS220-60		Sobreprecio para versión 220V/60Hz		Price Increase Power supply 220V/60Hz										
	SOVVCAS1/2		Sobreprecio para cajonera 2 cajones 1/2		Price increase for Block of 2 x 1/2 drawers										
	SOVCAS1/3		Sobreprecio para cajonera 3 cajones 1/3		Price increase for Block of 3 x 1/3 drawers										

**** Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

* Condiciones ambiental de funcionamiento: MÁX humedad 65% MÍN temperatura 25°C

Los gases fluorados de efecto invernadero están contenidos en equipos cerrados herméticamente.

Datos técnicos y características sujetas a cambio sin aviso previo.

**** Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

* Environment conditions: 65% humidity MAX MIN temperature 25 ° C

Fluorinated greenhouse refrigerant gases are contained in hermetically sealed equipment.

All specifications are subject to change without notice.



TRK 602/3/4R




Mesas ventiladas sobre patas profundidad 600 mm, de acero INOXIDABLE AISI 304; 2, 3, 4 compartimientos para rejillas 430x325 mm, con 1 rejilla plastificada para puerta o cajones de 1/2 o de 1/3.

- Grupo remoto
- Encimera recta, con alzada o sin encimera
- Controlador digital
- Descongelación y evaporación del agua de condensación automáticos (mod. incorporados)

S/s AISI 304 ventilated refrigerated counters on feet, 600 mm of depth; 2, 3 or 4 doors for 430x325 mm shelves, with 1 plastic coated shelf per door or 1/2 or 1/3 drawers.

- Remote unit
- Versions with straight worktop, worktop with splashback or without top
- Digital controller
- Automatic systems for defrosting and evaporation of the condensation water (only models with built-in unit)

OPTIONALS



74768132



SOVVCAS1/2600



SOVCAS1/3600



	Modelo <i>Model</i>	Código <i>Code</i>	Encimera <i>Worktop</i>	Rango <i>Range</i>	GAS <i>GAS</i>	Dimensiones <i>Dimensions</i> mm	Absorción <i>Absorbed power</i>		Voltaje <i>Voltage</i> Volt/Ph/Hz	Dimensiones embalaje <i>Packing dimensions</i> mm	Peso Neto/Bruto <i>Net/Gross weight</i> Kg
							Watt****	A			
	TRK602 R TN	9TRK62RPVA001	Encimera recta - <i>With work top</i>	0/+8° C		1040x600x850	0	0	230/1/50	1320x750x1100	65/85
	TRK602 R TN/A	9TRK62RPLA001	Encimera + alzada - <i>With work top with splashback</i>	0/+8° C		1040x600x950	0	0	230/1/50	1320x750x1100	65/85
	TRK602 R TN/S	9TRK62RPNA001	Sin encimera - <i>Without work top</i>	0/+8° C		1040x600x810	0	0	230/1/50	1320x750x1100	65/85
	UCTN1-T*	74861750	Unidad Condensadora / <i>Condensing unit</i>			350x460x265	332	5,54	230/1/50	350x460x265	23/43
	VALVR452A-602TN	74877075	Válvula R452A para modelo remoto (suministrada desmontada) (mod. 602TN)	<i>R452A Valve for remote model (supplied not installed) (mod. 602TN)</i>		101x38x77				101x38x77	0,3/0,3
	TRK603 R TN	9TRK63RPVA001	Encimera recta - <i>With work top</i>	0/+8° C		1500x600x850	0	0	230/1/50	1760x750x1100	75/110
	TRK603 R TN/A	9TRK63RPLA001	Encimera + alzada - <i>With work top with splashback</i>	0/+8° C		1500x600x950	0	0	230/1/50	1760x750x1100	85/112
	TRK603 R TN/S	9TRK63RPNA001	Sin encimera - <i>Without work top</i>	0/+8° C		1500x600x810	0	0	230/1/50	1760x750x1100	85/112
	UCTN2-T*	74861752	Unidad Condensadora - <i>Condensing unit</i>			350x460x 65	665	8,4	230/1	350x460x 65	25/45
	VALVR452A-603TN	74877075	Válvula R452A para modelo remoto (suministrada desmontada) (mod. 603TN)	<i>R452A Valve for remote model (supplied not installed) (mod. 603TN)</i>		101x38x77				101x38x77	0,3/0,3
	TRK604 R TN	9TRK64RPVA001	Encimera recta - <i>With work top</i>	0/+8° C		1960x600x850	0	0	230/1/50	2250x750x1100	95/125
	TRK604 R TN/A	9TRK64RPLA001	Encimera + alzada - <i>With work top with splashback</i>	0/+8° C		1960x600x950	0	0	230/1/50	2250x750x1100	95/125
	TRK604 R TN/S	9TRK64RPNA001	Sin encimera - <i>Without work top</i>	0/+8° C		1960x600x810	0	0	230/1/50	2250x750x1100	100/132
	UCTN3-T*	74861754	Unidad Condensadora / <i>Condensing unit</i>			350x500x300	665	8,4	230/1/50	350x500x300	33/53
	VALVR452A-604TN	74877077	Válvula R452A para modelo remoto (suministrada desmontada) (mod. 604TN)	<i>R452A Valve for remote model (supplied not installed) (mod. 604TN)</i>		101x38x77				101x38x77	0,3/0,3
		74768132	Rejilla plastificada 430x325	<i>Plastic coated 430x325 shelf</i>							
		74701947 P600 x2	Par guías acero inoxidable (450 mm)	<i>S/s pairs of runners (450 mm)</i>							
	VERS220-60		Sobrepeso para versión 220V/60Hz	<i>Price Increase Power supply 220V/60Hz</i>							
	SOVVCAS1/2		Sobrepeso para cajonera 2 cajones 1/2	<i>Price increase for Block of 2 x 1/2 drawers</i>							
	SOVCAS1/3		Sobrepeso para cajonera 3 cajones 1/3	<i>Price increase for Block of 3 x 1/3 drawers</i>							

* Distancia máxima 10 mt ** R = Versión remota **** Watt TN (-10/+45°C)

Los gases fluorados de efecto invernadero están contenidos en equipos cerrados herméticamente.

Datos técnicos y características sujetas a cambio sin aviso previo.

*Max distance 10 mt ** R = Remote Version **** Watt TN (-10/+45°C)

Fluorinated greenhouse refrigerant gases are contained in hermetically sealed equipment.

All specifications are subject to change without notice.